

LUCERE ENCAPSULATED SPECIFICATIONS

SHEET SIZES	48" X 120" (3050mm x 1220mm), 48" X 96" (2440mm x 1220mm) & 39" X 78" (2000mm x 1000mm) Not all designs available in all sheet sizes
THICKNESSES	¼"(6mm), ⅜" (9mm) & ½ (12mm) Not all designs available in all thicknesses
SURFACE FINISH	Gloss, Matt or Gloss / Matt
CUSTOMISABLE	Design - 10 sheet minimum
INDOOR / OUTDOOR	Indoor use only
WET AREAS	Yes - edges must be sealed
FABRICATION	Standard wood-working tools (excluding Alchemy and Fency)
THERMOFORMABLE	Most designs - contact your nearest Crown branch for details
INSTALLATION	An expansion gap of 1/16" per 36" (1mm per 1 metre) of product should be allowed for when setting out your sheets. Most glass fittings can be used
REFINISHABLE	Fully refinishable to Gloss or Matt
LEAD TIME	8 - 10 weeks. Express delivery is available subject to a surcharge.
CARE INSTRUCTIONS	In most instances, warm water, mild detergent, and a soft sponge, cloth or chamois will be enough to clean Lucere.
ENVIRONMENTAL INFORMATION	Easily recycled. Contact your nearest Crown branch for details
ADDITIONAL COMMENTS	<ol style="list-style-type: none">1. Being handmade, slight imperfections in Lucere are deemed acceptable. These slight imperfections may include small bubbles in the interlayer or slight surface texture imperfections. Any imperfection that is not visible 36" (1 meter) away from the panel is deemed within commercial tolerance.2. Lucere sheets may not be perfectly flat. Due to this, it is always suggested that the sheet be fully framed or mechanically fixed.3. Natural products used in Lucere are seasonal. As such, variations in colour and density may occur between samples and the order. If this detail is critical, a sample of current stock should be produced for final approval which will add up to 3 weeks to the ordering process.4. Lucere can be used as a splashback but NOT behind a stove or cooktop. We recommend a minimum distance of 12" (300mm) from stove or cooktop.